



TUGERO

GAMA HOME



3 AÑOS
GARANTÍA
TOTAL
COMPROMISO DE CALIDAD



A⁺
SCOP

A⁺⁺
SEER

A⁺⁺⁺
SCOP
Warmer

21dB
SEGUNDO O MODELO



Ficha técnica

SPLIT 1X1
SERIE SURE



Protección
Golden Fin

Temporizador
24 h

Función
I feel

Bomba de calor
8°C

Deshumidificador

Modo
silencioso

		GES26SUREWF		GES35SUREWF		GES52SUREWF		GES71SUREWF		
		IU	GES26SUREWF-I		GES35SUREWF-I		GES52SUREWF-I		GES71SUREWF-I	
MODELOS		OU	GES26SUREWF-O		GES35SUREWF-O		GES52SUREWF-O		GES71SUREWF-O	
CÓDIGO EAN			8435483850095		8435483850125		8435483850156		8435483850200	
Alimentación eléctrica		V,FHz	220~240V (1 Fase ~ 50Hz)							
Conexión			Unidad exterior							
RENDIMIENTO										
Capacidad refrigeración	Capacidad	kW	2,6 (0,9 - 3,39)		3,5 (1,11 - 4,16)		5,2 (0,34 - 5,83)		7,1 (2,08 - 7,95)	
		Btu/h	9.000 (3.100~11.600)		12.000 (3.800~14.200)		18.000(11.570~19.900)		24.000(7.100~27.000)	
	Consumo	W	732 (100~1.240)		1.213 (130~1.580)		1.500(560~2.050)		2.600(420~3150)	
	SEER	-	6,3		6,1		7,4		6,1	
	Clasificación energética	Frío	A++		A++		A++		A++	
Capacidad calefacción	Capacidad	kW	2,91 (0,82 - 3,37)		3,8 (1,08 - 4,22)		5,56 (3,1 - 5,85)		7,3 (1,61 - 7,95)	
		Btu/h	10.000 (2.800~11.500)		13.000 (3.700~14.400)		19.000 (10.580~19..960)		25.000 (5.500~27.000)	
	Consumo	W	733 (120~1.200)		1.088 (100~1.680)		1.570 (780~2.000)		2.400 (300~2.750)	
	SCOP	-	4		4		4		4	
	Clasificación energética	Calor	A+		A+		A+		A+	
CARACTERÍSTICAS										
Unidad interior	Potencia sonora	dB(A)	54		55		56		59	
	Presión sonora (H/M/L)	dB(A)	38,5/32/25/21		40,5/34,5/25/22		42,5/36/26/25		44,5/42/36/28	
	Caudal de aire	m³/h	466/360/325		540/430/314		840/680/540		980/817/662	
	Temperatura de operación	°C	16 ~ 31		16 ~ 31		16 ~ 31		16 ~ 31	
Unidad exterior	Potencia sonora	dB(A)	62		63		63		67	
	Presión sonora	dB(A)	55,5		56		56		59	
	Caudal de aire	m³/h	1.750		1.800		2.100		3.500	
	Temperatura de operación	°C	(-15 ~ 50) / (-15 ~ 30)		(-15 ~ 50) / (-15 ~ 30)		(-15 ~ 50) / (-15 ~ 30)		(-15 ~ 50) / (-15 ~ 30)	
Refrigerante	Compresor		GMCC		GMCC		GMCC		GMCC	
	Tipo/Carga	R32/Kg	0,55		0,55		1,08		1,42	
	Carga adicional >5	g/m	12		12		12		24	
DIMENSIONES Y PESO										
Unidad interior	Dimensiones netas (An×Al×Pr)	mm	805x285x194		805x285x194		957x302x213		1040x327x220	
	Dimensiones brutas (An×Al×Pr)	mm	870x365x270		870x365x270		1035x385x295		1120x405x315	
	Peso neto / bruto	Kg	7,6/9,7		7,6/9,7		10/13		12,3/15,8	
Unidad exterior	Dimensiones netas (An×Al×Pr)	mm	720x495x270		720x495x270		805x554x330		890x673x342	
	Dimensiones brutas (An×Al×Pr)	mm	835x540x300		835x540x300		915x615x370		995x740x398	
	Peso neto/bruto	Kg	23,2/25		23,2/25		32,7/35,4		42,9/45,9	
CONEXIONES										
Tubería frigorífica	Líquido - Gas	Pulg.	1/4" - 3/8"		1/4" - 3/8"		1/4" - 1/2"		3/8" - 5/8"	
	Longitud máx.	m	25		25		30		50	
	Desnivel máx.	m	10		10		20		25	
Conexiones eléctricas	Alimentación	mm	2 x 2,5 + T		2 x 2,5 + T		2 x 2,5 + T		2 x 2,5 + T	
	Interconexión	mm	4 x 2,5 + T		4 x 2,5 + T		4 x 2,5 + T		4 x 2,5 + T	